

# CONTENTS

## REVIEWED ARTICLES

- 160 **Modeling the Effect of Nail Corrosion on the Lateral Strength of Joints** by Samuel L. Zelinka and Douglas R. Rammer
- 167 [Technical Note] **A Comparison of Geometry Effect on Tensile Testing of Wood Strands** by Neil Kohan, Brian K. Via, and Steven Taylor
- 171 **Effect of Moisture Sorption State on Vibrational Properties of Wood** by Jianxiong Lu, Jiali Jiang, Yiqiang Wu, Xianjun Li, and Zhiyong Cai
- 177 **Protocol Comparison: Laboratory versus Natural Weathering Tests for Performance Evaluation of Coatings on Preservative-Treated Wood** by Mojgan Nejad, Tony Ung, and Paul Cooper
- 184 **Effects of Outdoor Exposure Angle on the Deterioration of Wood-Based Board Properties** by Hideaki Korai, Noboru Sekino, and Hiroshi Saotome
- 191 **Examination of the Specimen Configuration and Analysis Method in the Flexural and Longitudinal Vibration Tests of Solid Wood and Wood-Based Materials** by Hiroshi Yoshihara
- 201 **Dynamic Mechanical Properties of Polymeric Diphenylmethane Diisocyanate/Bio-Oil Adhesive System** by An Mao and Sheldon Q. Shi
- 207 **Effects of Melamine on the Properties of Medium-Density Fiberboard Fabricated with Urea-Based Resins** by Sang-Min Lee, Jong-Young Park, Sang-Bum Park, and Won-Joung Hwang
- 214 **China's Wood Furniture Manufacturing Industry: Industrial Cluster and Export Competitiveness** by Yang Hongqiang, Ji Chunyi, Nie Ying, and Hong Yinxing
- 222 **A Productivity and Cost Comparison of Two Systems for Producing Biomass Fuel from Roadside Forest Treatment Residues** by Nathaniel Anderson, Woodam Chung, Dan Loeffler, and John Greg Jones
- 234 **Effect of *Pinus radiata* Bark Polyphenols on Phenol Liquefaction of Cellulose in the Presence of *p*-Toluene Sulfonic Acid Catalyst** by Sung Phil Mun, Jeong Phil Jang, and Moon G. Kim

## ERRATUM

In the article "Borate and Imidacloprid Treatment of Ash Logs Infested with the Emerald Ash Borer" by Nzokou et al., *Forest Products Journal* 56(5):78–81, an incorrect factor was used to convert the DOT% (percent disodium octaborate tetrahydrate) to BAE (boric acid equivalent). The correct conversion factor is  $BAE = 1.2 \times \%DOT$ , because boric acid is 56% boric oxide and DOT is 67% boric oxide. The corrected version of Table 1 is below. Changed values are shown in **bold**.

Table 1.—Borate and imidacloprid concentrations evaluated to reduce EAB emergence from infested ash logs maintained indoors.<sup>a</sup>

Insecticide		Concentration tested			
		----- (%) -----			
Borate	DOT	6.60	4.90	2.45	1.22
	BAE	<b>7.92</b>	<b>5.88</b>	<b>2.94</b>	<b>1.46</b>
Imidacloprid		0.05	0.03	0.02	0.01

<sup>a</sup> DOT = disodium octaborate tetrahydrate; BAE = boric acid equivalent.

References to BAE in Tables 2 and 3, and throughout the text of the article, should be modified according to the changes shown in the corrected version of Table 1 presented here.